

Slickline & Stuffing Box Sheaves



Our Slickline Family of sheaves offers a wide range of sizes, styles, and materials to fit all your Slickline, Flat-pack, and Encapsulated Line operation needs. Featuring a lightweight composite wheel, high-strength aluminum, and stainless steel components our sheaves are designed to handle all your critical operations in the harshest conditions. The user friendly side-loading system and roller shrouds on our slickline sheaves, and patented top-loading system on our Stuffing Box Sheaves prevents your line from “jumping sheave” and keeps it where it belongs...in the groove.

Our Slickline Sheaves range in wheel sizes from 16" to 30", and can handle a variety of line sizes, while the Flat-pack Sheave is available in either a 25" or 30" wheel.

Our Stuffing Box Sheave is available in two wheel sizes, 16" and 20", and can be manufactured with either an aluminum or stainless steel base and frame.

Optional items like our hand guard, line wiper, and floor stand will not only improve the user experience but will greatly increase safety to the operator. Each sheave comes fully certified with 4:1 safety factor and a one-year manufactures guarantee.

16", 20", 25", & 30" Slickline Sheaves

WHEEL SIZE	16	20	25	30
HEIGHT	26"	30"	38"	43"
WEIGHT	20 lbs.	23 lbs.	75 lbs.	95 lbs.
CABLE DIAMETER	Up to 5/32"	Up to 5/32"	Up to 3/16"	Up to 3/16"
MAXIMUM SWL	6,000	6,000	10,000	10,000
PROOF TEST LOAD	12,000	12,000	20,000	20,000
SAFETY FACTOR	4:1	4:1	4:1	4:1

16" AND 20" STUFFING BOX SHEAVE - ALUM

WHEEL SIZE	16-Alum	20-Alum	16-SS	20-SS
HEIGHT	31"	35"	31"	35"
WEIGHT	30 lbs.	35 lbs.	51 lbs.	54 lbs.
CABLE DIAMETER	Up to 5/32"	Up to 5/32"	Up to 5/32"	Up to 5/32"
MAXIMUM SWL	6,000	6,000	6,000	6,000
PROOF TEST LOAD	12,000	12,000	12,000	12,000
SAFETY FACTOR	4:1	4:1	4:1	4:1